

LCS2

ROBUST MULTI-PROTOCOL READER WITH BACKLIT KEYS

LCS2 is a multi-protocol reader with backlit keys that needs to be connected to a Host. Wiegand 26, 30, 34 or 40-bit, Data/Clock or CODIX protocol chosen directly from the keypad. Available in various colours it can be surface or flush mounted.



FEATURES

- Multi-protocol robust reader
- Backlit metal/plastic keys
- Protocol chosen directly from the keypad
- Compatible with Wiegand 26, 30, 34, 40bit or Data/Clock
- Bi-directional CODIX protocol for networking with XPR's Master units
- Red and Green LEDs provide remote information
- Audible and Visual feedback

SPECIFICATIONS

Electrical Characteristics:

Operating Voltage:	12V DC
Current consumption:	Standby: 5 mA; Max.: 30 mA
Keypad Lighting:	Backlit for 10 seconds for each press of keys
Visible Signals:	Green and red leds: free tension led
Yellow led:	Status
Audible Signal:	1 internal buzzer

Environmental Characteristics:

Operating Temperature:	-20°C to 50°C
Operating Humidity:	0 to 95% (non-condensing)

REFERENCES



LCS2-43B



LCS2-72C



LCS2-102A



LCS2M-43B



LCS2M-72C



LCS2M-102A




LCS2-62A




LCS2M-62A


DIMENSIONS




43B



72C



102A



62A